



Prodotti attacco velcro / Velcro attachment products










777F

DISCHI VELCRATI OSSIDO ALLUMINIO CERAMICO 777F CERAMIC ALUMINUM OXIDE VELCRO DISCS 777F **3M**

Tela resinata peso Y poliestere ossido di alluminio ceramico + additivo raffreddante. Indicato per applicazioni con smerigliatrici angolari su acciai inox, titanio, alluminio e metalli in genere.

Resin bonded Y polyester cloth ceramic aluminum oxide + cooling filler. Suitable for applications with right-angle sanders on stainless steel, titanium, aluminum and metals.

DIMENSIONI SIZES MM	GRANE GRITS	FORATURA HOLE PATTERN	CODICE ART. ITEM CODE		
50	40	 SENZA FORI NO HOLES	VDC050SFD	30	
	60		VDC050SFF	50	
	80		VDC050SFG	50	
	100		VDC050SFH	50	
	120		VDC050SFI	50	
75	40	 SENZA FORI NO HOLES	VDC075SFD	30	
	60		VDC075SFF	50	
	80		VDC075SFG	50	
	100		VDC075SFH	50	
	120		VDC075SFI	50	
115	40	 SENZA FORI NO HOLES	VDC115SFD	30	
	60		VDC115SFF	50	
	80		VDC115SFG	50	
	100		VDC115SFH	50	
	120		VDC115SFI	50	
125	40	 SENZA FORI NO HOLES	VDC125SFD	30	
	60		VDC125SFF	50	
	80		VDC125SFG	50	
	100		VDC125SFH	50	
	120		VDC125SFI	50	
150	40	 SENZA FORI NO HOLES	VDC150SFD	30	
	60		VDC150SFF	50	
	80		VDC150SFG	50	
	100		VDC150SFH	50	
	120		VDC150SFI	50	
200	40	 SENZA FORI NO HOLES	VDC200SFD	30	
	60		VDC200SFF	50	
	80		VDC200SFG	50	
	100		VDC200SFH	50	
	120		VDC200SFI	50	

Per ulteriori formati e dimensioni Vi preghiamo chiedere la quotazione relativa.
For further sizes and conversions please ask for the quotation.