RUOTE IN SPUGNA NEOPRENE LISCIO / PLANE NEOPRENE WHEELS

Ruota rivestita da NEOPRENE liscio. Altezza standard del rivestimento 45/50 mm circa. Grazie alla particolare morbidezza di questo rivestimento (15/18 SHORE A circa), la ruota si adatta perfettamente ad operazioni di finitura su tutti i metalli teneri (es. ottone, alluminio, zama, bronzo ecc.) permettendo allo stesso tempo di seguire i più svariati profili. E' necessario rispettare il senso e la velocità di rotazione riportate sulla ruota. Può essere montata su macchine manuali, automatiche ed impianti robotizzati.

Wheel covered with plane NEOPRENE. Standard width of the cover is around 45/50mm. Thanks to the particular softness of this cover (around 15/18 Shore A), this wheel is suitable for finishing operations on all soft metals (e.g. brass, aluminum, zamak, bronze, etc.) allowing, in the same time, to follow the most different profiles. Rotation direction and maximum operating speed indicated on the wheel must be respected. It can be mounted on manual and automatic machines and robots.

D \ H	30	40	50	60	70	80	90	100	120	150
200										
250										
300										
350										
400										
450										
450										

Durezze disponibili/Available hardnesses:Shore A 15/18

SOLO RIVESTIMENTO RUOTE IN SPUGNA NEOPRENE LISCIO

PLANE NEOPRENE WHEELS RIGENERATION

D \ H	30	40	50	60	70	80	90	100	120	150
200										
250										
300										
350										
400										
450										
450										